10-24 UNC 2B 4X 4X Ø.203 EQ SPACED ON EQ SPACED ON A Ø 2.625 B.C. 2.436±.015 1.000 A Ø 2.625 B.C. .50 THRD DEPTH .312 #303 WOODRUFF 1.500 (f)ď Ο С 2.250 .3750 .3745 (f) \bigcirc Ο Ο Ο - .062 .225 -Ø.251 Ø 3.050 UNLESS OTHERWISE SPECIFIED: CARSON MFG INC DIMENSIONS ARE IN INCHES 5001 GRUMMAN DR CARSON CITY, NV 90706 TWO PLACE DECIMAL ±.010 TYPE 23 SP RATIO THREE PLACE DECIMAL ±.005 4:1-10:1 FOUR PLACE DECIMAL ±.001 BREAK SHARP CORNERS .015 DRAWN DATE TITLE: MAX FILLET RADIUS .015 9/19/12 CARSON MFG. INC KRP SURFACE FINISH 32 COMMENTS HEAT TREAT N/A PROPRIETARY AND CONFIDENTIAL MATERIAL SIZE DWG. NO. REV THE INFORMATION CONTAINED IN THIS N/A DRAWING IS THE SOLE PROPERTY OF 23SPSINGLE Α FINISH CARSON MFG INC. ANY N/A REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF DO NOT SCALE DRAWING SCALE: 1:1 WEIGHT: SHEET 1 OF 1 CARSON MFG INC. IS PROHIBITED. 5 3 2 4